

Application No. 10/090,503

Attorney Docket No. 10541-453

I. Listing of Claims

1. (Currently Amended): A method of forming a trim part having an outer surface exposed to an interior of a motor vehicle and an inner surface for attaching the trim part to an interior sheet in a motor vehicle, the method comprising:

providing a substrate having a first side, and a second side, and a periphery connecting the first side and the second side;

disposing the substrate in a molding tool, wherein the molding tool has an upper mold and a lower mold;

engaging the first side of the substrate with the upper mold;

engaging the second side of the substrate with the lower mold;

compression molding the first side of the substrate such that the first side forms the outer surface of the trim part; and

injection molding an attachment surface to the second side of the substrate such that the second side forms the inner surface of the trim part, the attachment surface continuously extending along the second side of the substrate adjacent to the periphery of the substrate, wherein the attachment surface has at least one attachment boss boss extending from the attachment surface to attach the trim part to the interior sheet.

2. (Original): The method of Claim 1 further comprising the step of:

providing a gate on the lower mold;

attaching at least one surface runner to the gate;

injecting a resin through the gate into the surface runner;

directing the flow of the resin through the surface runner to the second side of the substrate;

forming the attachment surface by injection molding the resin on the second side of the substrate.

3. (Original): The method of Claim 2 further comprising curing the resin to form the attachment surface extending from the second side to attach the trim part to the interior sheet.

-2-



BRINKS HOFER GILSON & LIONE
PO Box 10395
Chicago, IL 60611-5599

Application No. 10/090,503

Attorney Docket No. 10541-453

4. (Original): The method of Claim 2 wherein the resin is a polypropylene resin.
5. (Original): The method of Claim 1 wherein the attachment surface extends along a periphery of the second side of the substrate.
6. (Original) The method of Claim 1 further comprising injection molding ribs on the second side of the substrate, the ribs extending perpendicular to the attachment surface.
7. (Currently Amended): The method of Claim ~~[[5]]~~ 6 further comprising forming the ribs adjacent to the attachment ~~besses~~ boss on the second side of the substrate.
8. (Previously Presented): The method of Claim 1 further comprising selecting the substrate from a group consisting of natural fiber/Thermoplastic composite or a woodstock/thermoplastic composite material.
9. (Previously Presented): The method of Claim 1 further comprising the step of pre-heating the substrate to a temperature in the range of 380 F to 410 F before disposing the substrate on to the molding tool.
10. (Previously Presented): The method of Claim 1 further comprising simultaneously compression molding the first side of the substrate and injection molding the attachment surface on the second side of the substrate.
11. (Currently Amended): The method of Claim 1 wherein the at least one attachment ~~besses-include~~ boss includes at least one locating boss and at least one heat stake boss extending from the second side to attach the trim part to the interior sheet.

-3-

**BRINKS
HOFER
GILSON
& LIONE**BRINKS HOFER GILSON & LIONE
PO Box 10395
Chicago, IL 60611-5599

Application No. 10/090,503

Attorney Docket No. 10541-453

12. (Currently Amended): The method of Claim 1 wherein at least one of the at least one attachment bosses boss has a substantially circular cross-section.

13. (Cancelled)

14. (Cancelled)

15. (Cancelled)